



# ANTI-SLIP

## ANTI-SLIP STEP COVER



Highly versatile, heavy duty pre-formed step covers and nosing. Robust GRP provides a corrosion resistant surface for damaged, worn or slippery steps. Anglo Anti-Slip Step Cover will tolerate heavy wear and has excellent slip resistance even in wet conditions.



Two sizes available.  
600 x 220mm  
1000 x 220mm

## ANTI-SLIP TAPE



Instant anti-slip surfaces for steps, ramps, floors, vehicles, boats etc. Available in Yellow, White, Black, Hazard, and Clear. Anglo Anti-Slip Tape 'Aqua' (White) is available for barefoot areas such as showers, pool surrounds etc.



Rolls approx. 18m x 50mm.

## ANTI-SLIP TREAD



These self-adhesive treads are easily applied to most smooth surfaces. They provide an anti-slip finish to improve safety on concrete, metal or wood surfaces.



Available in Black.

Tread size 610mm x 150mm.

Anglo also offers a range of anti-slip coatings – please call 02476 717 329 for details.

# PRODUCT INFORMATION

## ANTI-SLIP STEP COVER

### AVAILABILITY

Anglo Anti-Slip Step Covers are available in two sizes 600 x 220mm and 1000 x 220mm.

### SURFACE PREPARATION

Patch repair badly damaged or dished steps using a suitable filler or strong cement mix. Anglo Epoxy Repair Mortar is ideal if heavy use is anticipated.

### APPLICATION

Dry fit the tread to ensure that it is the correct size and lays flat on the surface. If required it can be trimmed to size using an industrial jigsaw and appropriate cutting blades (Bosch TIOI AIF or similar are ideal). The tread is pre-drilled for mechanical fixing to damp, dirty or friable surfaces.

### We recommend the following fixings:

**To timber:** 30mm x 5mm zinc plated or stainless steel screws.

**To steel plate:** No.8 x 20mm self-tapping pan head Pozi stainless steel screws or No.8 x 20mm self-drilling pan head Philips zinc plated screws.

**To concrete:** 30mm x 5mm zinc plated or stainless steel impact anchors (Hilti HPS-1 or similar).

**To open mesh:** stainless steel or zinc plated saddle clips and dome head bolts suitable in length for the depth of the existing treads. Alternatively, the tread can be glued to sound, clean, dry surfaces using a suitable high strength gap filling adhesive (Gripfill or similar).

## ANTI-SLIP TAPE

### AVAILABILITY

Anglo Anti-Slip Tapes are available in 18m x 50mm rolls in Yellow, White, Black, Hazard and Clear. Anglo Anti-slip Tape 'Aqua' (White) is available for barefoot areas only such as showers, pool surrounds etc.

### SURFACE PREPARATION

The surface must be clean, dry and smooth.

### PRIMING

Anglo Anti-Slip Tape can be applied directly onto clean, smooth, non-porous surfaces. We recommend that Anglo Anti-Slip Primer is used to improve adhesion and durability on porous surfaces.

### APPLICATION

Apply at temperatures above 10°C. Peel off backing strip and firm into place using foot pressure or soft rubber mallet. The tape can be walked on immediately but maximum adhesion is achieved after approximately 24 hours. Anglo Anti-Slip Edge Sealer is recommended in wet or heavy wear conditions (see below).

### LIMITATIONS

Anglo Anti-Slip Edge Sealer and Anglo Anti-Slip Primer are not recommended for use with Anglo Anti-Slip Tape 'Aqua'.

## ANTI-SLIP TREAD

### AVAILABILITY

Anglo Anti-Slip Treads measure approximately 150mm x 610mm wide.

### SURFACE PREPARATION

The surface must be clean, dry and smooth.

### PRIMING

Anglo Anti-Slip Treads can be applied directly onto clean, smooth, non-porous surfaces. We recommend that Anglo Anti-Slip Primer should be used to improve adhesion and durability on porous surfaces.

### APPLICATION

Apply at temperatures above 10°C. Peel off backing strip and firm into place using foot pressure or soft rubber mallet. Anglo Anti-Slip Treads can be walked on immediately after application and maximum adhesion is achieved after approximately 24 hours.

Anglo Anti-Slip Edge Sealer is recommended in wet or heavy wear conditions (see below).

## ANTI-SLIP PRIMER

Anglo Anti-Slip Primer for Anglo Anti-Slip Tape and Anglo Anti-Slip Treads improves adhesion especially on porous surfaces. Most non-porous surfaces do not usually require a primer. Do not apply primer to steel or other metal surfaces.

### SURFACE PREPARATION

Ensure the surface is clean, dry and sound.

### APPLICATION

After stirring, apply one coat of primer by brush at a coverage rate of approximately 2-3m<sup>2</sup> per 500ml. Allow to dry (approximately 1 hour at 10-15°C). The product is milky when applied, then turns clear upon drying. Only apply the primer to the area that will be covered by the tape or tread. Uncovered primer will remain tacky and attract dirt. Apply the Anglo Anti-Slip Tapes and Anglo Anti-Slip Treads according to the instructions.

### LIMITATIONS

Do not apply in wet conditions or at temperatures below 10°C. Anglo Anti-Slip Primer is not recommended for use with Anglo Anti-Slip Tape 'Aqua'.

## ORDERING

Available from stockists throughout the UK and from distributors worldwide. All Anglo products are sold subject to the Company's Standard Conditions of Sale.

The Company and its representatives are often asked to comment on potential uses of Anglo products which differ from those described in the Company's data sheets. Whilst in such cases the Company and its representatives will always try to offer helpful and constructive advice, the Company cannot be held responsible for the results of such uses unless they are specifically confirmed in writing by Anglo.

All information is based on results gained from experience and tests and is believed to be accurate, but is given without acceptance of liability for loss or damage attributable to reliance thereon as conditions of use lie outside our control.

## ANTI-SLIP EDGE SEALER

Anglo Anti-Slip Edge Sealer may be used to seal and help protect the edges of Anglo Anti-Slip Tape and Anglo Anti-Slip Tread in wet or heavy wear conditions.

### APPLICATION

Apply Anglo Anti-Slip Edge Sealer direct from the tube to seal edges of the Anglo Anti-Slip Tape or Anglo Anti-Slip Tread.

### LIMITATIONS

Not suitable for application to Anglo Anti-Slip Tape 'Aqua'.

**WWW.ANGLOBUILD.CO.UK**

**Rust-Oleum UK Ltd.**

Unit 6, Spitfire Close, Coventry Business Park, Coventry, CV5 6UR, United Kingdom  
T +44 (0)2476 717 329 F +44 (0)2476 718 930 [info.uk@ro-m.com](mailto:info.uk@ro-m.com) [www.ro-m.com](http://www.ro-m.com)