




# ASPHALT RESTORER

**A single application, black and tile red refurbishing coating for car parks, driveways and footpaths**



**Anglo Asphalt Restorer** provides an 'as new' appearance that will mask old line markings and repairs and will hide ingrained dust from building works etc.

- **Upgrades drab, grey, stained asphalt**
- **Covers old line markings and repairs**
- **Avoids disruptive and costly re-surfacing**



# **PRODUCT INFORMATION**

## **AVAILABILITY**

Anglo Asphalt Restorer is available in 5 litre tins.

## **COMPOSITION**

Top quality bitumen with flow agents and high grade filler.

## **SURFACE PREPARATION**

Surfaces should be dry and free of any loose material. Moss etc., should be removed by scraping and/or jet washing and the surface left to dry thoroughly.

## **APPLICATION**

Stir thoroughly before use. The product should be applied generously but evenly in one coat using a roller or brush. Small pits and fissures can be filled with a stiff mortar consisting of dry sand mixed with the product. Pits and fissures should be primed with the product before trowelling in the mortar.

## **COVERAGE**

5-10m<sup>2</sup> per 5 litres.

## **CURING TIME**

Approximately 2-5 hours at 5°C to 20°C. Rain will delay curing by trapping solvents within the coating. Protect from rain for at least 30 minutes after application.

## **CLEANING APPLICATORS**

Use white spirit or similar solvent.

## **LIMITATIONS**

This product is intended as a surface coating. It is not designed to strengthen or repair weak or damaged surfaces. This product is designed for use on bitumen based surfaces. It could soften surfaces which contain coal tar. If in doubt, apply a test area and check after 24 hours that no softening has occurred.

## **STORAGE**

Store away from sources of heat or ignition.

## **SAFETY**

All product labels provide general safety information. A Material Safety Data Sheet is available.

## **ORDERING**

All Anglo products are sold subject to the Company's Standard Conditions of Sale. The Company and its representatives are often asked to comment on potential uses of Anglo products which differ from those described in the Company's data sheets. Whilst in such cases the Company and its representatives will always try to offer helpful and constructive advice, the Company cannot be held responsible for the results of such uses unless they are specifically confirmed in writing by the Company.

All information is based on results gained from experience and testing and is believed to be accurate, but it is given without acceptance of liability for loss or damage attributable to reliance thereon as conditions of use lie outside our control.

Available from stockists throughout the UK. For further information or your nearest stockist, please telephone our Technical Sales Department on +44(0)2476 717 329.

**WWW.ANGLOBUILD.CO.UK**

**Rust-Oleum UK Ltd.**

Unit 6, Spitfire Close, Coventry Business Park, Coventry, CV5 6UR, United Kingdom

T +44 (0)2476 717 329 F +44 (0)2476 718 930

*info.uk@ro-m.com www.ro-m.com*