



## SAFETY DATA SHEET

### Anglo Flexi-Joint Fill - resin

#### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME Anglo Flexi-Joint Fill - resin

SUPPLIER Anglo Building Products Ltd  
RUST-OLEUM UK Ltd  
Unit 6, Spitfire Close  
Coventry Business Park  
Coventry  
CV5 6UR  
+44 (0) 2476 717 329  
+44 (0) 2476 718 930  
info.uk@ro-m.com

#### 2 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

#### 3 COMPOSITION/INFORMATION ON INGREDIENTS

#### 4 FIRST-AID MEASURES

##### INHALATION

Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

##### INGESTION

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Get medical attention if any discomfort continues.

##### SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

##### EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

#### 5 FIRE-FIGHTING MEASURES

##### EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

#### 6 ACCIDENTAL RELEASE MEASURES

##### SPILL CLEAN UP METHODS

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer.

#### 7 HANDLING AND STORAGE

##### USAGE PRECAUTIONS

Avoid spilling, skin and eye contact.

##### STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

#### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

##### PROTECTIVE EQUIPMENT

## Anglo Flexi-Joint Fill - resin



### ENGINEERING MEASURES

Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of vapours.

### RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

### HAND PROTECTION

Use suitable protective gloves if risk of skin contact.

### EYE PROTECTION

If risk of splashing, wear safety goggles or face shield.

### OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

### HYGIENE MEASURES

**DO NOT SMOKE IN WORK AREA!** Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Viscous liquid		
COLOUR	Grey		
ODOUR	Mild		
SOLUBILITY	Insoluble in water		
RELATIVE DENSITY	1.3	VOLATILE ORGANIC COMPOUND (VOC)	<0.1%

## 10 STABILITY AND REACTIVITY

### STABILITY

Stable under normal temperature conditions.

### CONDITIONS TO AVOID

Avoid excessive heat for prolonged periods of time.

### HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## 11 TOXICOLOGICAL INFORMATION

### INHALATION

In high concentrations, vapours may irritate throat and respiratory system and cause coughing.

### INGESTION

May cause discomfort if swallowed.

### SKIN CONTACT

Liquid may irritate skin.

### EYE CONTACT

Spray and vapour in the eyes may cause irritation and smarting.

## 12 ECOLOGICAL INFORMATION

### ECOTOXICITY

Not regarded as dangerous for the environment.

## 13 DISPOSAL CONSIDERATIONS

### DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

## Anglo Flexi-Joint Fill - resin

---

### 14 TRANSPORT INFORMATION

---

GENERAL	The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).
	No transport warning sign required.
ROAD TRANSPORT NOTES	Not Classified
RAIL TRANSPORT NOTES	Not Classified.
SEA TRANSPORT NOTES	Not Classified.
AIR TRANSPORT NOTES	Not Classified.
MARINE POLLUTANT	No.

---

### 15 REGULATORY INFORMATION

---

RISK PHRASES

NC	Not classified.
----	-----------------

SAFETY PHRASES

NC	Not classified.
----	-----------------

STATUTORY INSTRUMENTS  
 Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE  
 Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

GUIDANCE NOTES  
 Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

---

### 16 OTHER INFORMATION

---

REVISION DATE                      08/12/2008  
 REV. NO./REPL. SDS GENERATED 1



## SAFETY DATA SHEET

### Anglo Flexi-Joint Fill - hardener

#### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME                    Anglo Flexi-Joint Fill - hardener

SUPPLIER                         Anglo Building Products Ltd  
 RUST-OLEUM UK Ltd  
 Unit 6, Spitfire Close  
 Coventry Business Park  
 Coventry  
 CV5 6UR  
 +44 (0) 2476 717 329  
 +44 (0) 2476 718 930  
 info.uk@ro-m.com

#### 2 HAZARDS IDENTIFICATION

Irritating to eyes, respiratory system and skin. May cause sensitisation by inhalation.

CLASSIFICATION                 R42. Xi;R36/37/38.

#### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
DIPHENYLMETHANEDIISOCYANATE -Isomers & homologues		9016-87-9	10-30%	Xn;R20. Xi;R36/37/38. R42.

The Full Text for all R-Phrases are Displayed in Section 16

#### 4 FIRST-AID MEASURES

##### INHALATION

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention.

##### INGESTION

DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Provide rest, warmth and fresh air. Get medical attention.

##### SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Rinse the skin immediately with lots of water. Get medical attention promptly if symptoms occur after washing.

##### EYE CONTACT

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

#### 5 FIRE-FIGHTING MEASURES

##### EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

#### 6 ACCIDENTAL RELEASE MEASURES

##### PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

##### SPILL CLEAN UP METHODS

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer.

#### 7 HANDLING AND STORAGE

##### USAGE PRECAUTIONS

Avoid spilling, skin and eye contact.

## Anglo Flexi-Joint Fill - hardener

**STORAGE PRECAUTIONS**

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

**STORAGE CLASS**

Chemical storage.

### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
DIPHENYLMETHANEDIISOCYANATE -Isomers & homologues	MEL		0.02 mg/m3(Sen)		0.07 mg/m3(Sen)

**PROTECTIVE EQUIPMENT**



**PROCESS CONDITIONS**

Provide eyewash station.

**ENGINEERING MEASURES**

Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of vapours.

**RESPIRATORY EQUIPMENT**

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

**HAND PROTECTION**

Use suitable protective gloves if risk of skin contact.

**EYE PROTECTION**

If risk of splashing, wear safety goggles or face shield.

**OTHER PROTECTION**

Wear appropriate clothing to prevent any possibility of skin contact.

**HYGIENE MEASURES**

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

### 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid	
COLOUR	Brown	
ODOUR	Mild	
SOLUBILITY	Insoluble in water	
RELATIVE DENSITY	1.2	VOLATILE ORGANIC COMPOUND (VOC) <0.1%

### 10 STABILITY AND REACTIVITY

**STABILITY**

Stable under normal temperature conditions.

**CONDITIONS TO AVOID**

Avoid excessive heat for prolonged periods of time.

**HAZARDOUS DECOMPOSITION PRODUCTS**

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).

### 11 TOXICOLOGICAL INFORMATION

**INHALATION**

May cause sensitisation by inhalation.

**INGESTION**

May cause stomach pain or vomiting.

**Anglo Flexi-Joint Fill - hardener****SKIN CONTACT**

May cause sensitisation by skin contact. Irritating to skin.

**EYE CONTACT**

Irritating to eyes.

**12 ECOLOGICAL INFORMATION****ECOTOXICITY**

Not regarded as dangerous for the environment.

**13 DISPOSAL CONSIDERATIONS****DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements.

**14 TRANSPORT INFORMATION****GENERAL**

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

No transport warning sign required.

**ROAD TRANSPORT NOTES**

Not Classified

**RAIL TRANSPORT NOTES**

Not Classified.

**SEA TRANSPORT NOTES**

Not Classified.

**AIR TRANSPORT NOTES**

Not Classified.

**MARINE POLLUTANT**

No.

**15 REGULATORY INFORMATION****LABELLING**

Harmful

**CONTAINS**

DIPHENYLMETHANEDIISOCYANATE -Isomers & homologues

**RISK PHRASES**

R36/37/38

Irritating to eyes, respiratory system and skin.

R42

May cause sensitisation by inhalation.

**SAFETY PHRASES**

S23

Do not breathe vapour/spray.

S24/25

Avoid contact with skin and eyes.

S26

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S37

Wear suitable gloves.

S38

In case of insufficient ventilation, wear suitable respiratory equipment.

S45

In case of accident or if you feel unwell, seek medical advice immediately (show label where possible).

S60

This material and its container must be disposed of as hazardous waste.

P4

Contains isocyanates. See information supplied by the manufacturer.

**STATUTORY INSTRUMENTS**

Chemicals (Hazard Information and Packaging) Regulations.

**APPROVED CODE OF PRACTICE**

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

**GUIDANCE NOTES**

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

**16 OTHER INFORMATION**

## Anglo Flexi-Joint Fill - hardener

REVISION DATE 08/12/2008

REV. NO./REPL. SDS GENERATED 1

### RISK PHRASES IN FULL

R20	Harmful by inhalation.
R36/37/38	Irritating to eyes, respiratory system and skin.
R42	May cause sensitisation by inhalation.



## SAFETY DATA SHEET

### Anglo Flexi-Joint Fill - primer

#### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME                    Anglo Flexi-Joint Fill - primer

SUPPLIER                         Anglo Building Products Ltd  
 RUST-OLEUM UK Ltd  
 Unit 6, Spitfire Close  
 Coventry Business Park  
 Coventry  
 CV5 6UR  
 +44 (0) 2476 717 329  
 +44 (0) 2476 718 930  
 info.uk@ro-m.com

#### 2 HAZARDS IDENTIFICATION

Flammable. Irritating to respiratory system. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION                    Xi;R37. N;R51/53. R10.

#### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
1,2,4-TRIMETHYLBENZENE	202-436-9	95-63-6	10-30%	R10 Xn;R20 Xi;R36/37/38 N;R51/53
CUMENE	202-704-5	98-82-8	1-5%	R10 Xn;R65 Xi;R37 N;R51/53
MESITYLENE	203-604-4	108-67-8	5-10%	R10 Xi;R37 N;R51/53
Solvent naphtha(petroleum), light aromatic,<0.1% benzene	265-199-0	64742-95-6	10-30%	Xn;R65. Xi;R37. N;R51/53. R10.

The Full Text for all R-Phrases are Displayed in Section 16

#### 4 FIRST-AID MEASURES

##### GENERAL INFORMATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

##### INHALATION

Move the exposed person to fresh air at once. For breathing difficulties oxygen may be necessary. If breathing stops, provide artificial respiration. Keep the affected person warm and at rest. Get prompt medical attention.

##### INGESTION

DO NOT INDUCE VOMITING! Remove victim immediately from source of exposure. Rinse mouth thoroughly. Provide rest, warmth and fresh air. Get medical attention immediately!

##### SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.

##### EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Contact physician if irritation persists.

#### 5 FIRE-FIGHTING MEASURES

##### EXTINGUISHING MEDIA

Fire can be extinguished using: Foam. Dry chemicals, sand, dolomite etc.

##### SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapours. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

#### 6 ACCIDENTAL RELEASE MEASURES

## Anglo Flexi-Joint Fill - primer

### SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Clean-up personnel should use respiratory and/or liquid contact protection. Absorb in vermiculite, dry sand or earth and place into containers.

## 7 HANDLING AND STORAGE

### USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Use explosion proof electric equipment.

### STORAGE PRECAUTIONS

Flammable/combustible - Keep away from oxidisers, heat and flames. Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

### STORAGE CLASS

Flammable liquid storage.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
CUMENE	OES	25 ppm(Sk)	125 mg/m3(Sk)	50 ppm(Sk)	250 mg/m3(Sk)

### PROTECTIVE EQUIPMENT



### ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

### RESPIRATORY EQUIPMENT

Respiratory protection must be used if air contamination exceeds acceptable level.

### HAND PROTECTION

Use protective gloves.

### EYE PROTECTION

Use approved safety goggles or face shield.

### OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

### HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid		
COLOUR	Brown		
ODOUR	Aromatic hydrocarbons		
SOLUBILITY	Insoluble in water		
BOILING POINT (°C)	>150C	RELATIVE DENSITY	0.99
FLASH POINT (°C)	43C	VOLATILE ORGANIC COMPOUND (VOC)	50%

## 10 STABILITY AND REACTIVITY

### STABILITY

Stable under normal temperature conditions.

### CONDITIONS TO AVOID

Avoid heat. Avoid contact with oxidisers or reducing agents.

### HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

## 11 TOXICOLOGICAL INFORMATION

## Anglo Flexi-Joint Fill - primer

**HEALTH WARNINGS**

INHALATION. May cause irritation to the respiratory system. Solvent vapours are hazardous and may cause nausea, sickness and headaches. SKIN CONTACT. Irritating to skin. Product has a defatting effect on skin. EYE CONTACT. Irritating to eyes. INGESTION. May cause discomfort.

**ROUTE OF ENTRY**

Inhalation. Skin absorption.

**12 ECOLOGICAL INFORMATION**

**13 DISPOSAL CONSIDERATIONS**

**DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements.

**14 TRANSPORT INFORMATION**



UK ROAD CLASS	3		
PROPER SHIPPING NAME	PAINT RELATED MATERIAL		
UN NO. ROAD	1263	UK ROAD PACK GR.	III
ADR CLASS NO.	3	ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	III	HAZARD No. (ADR)	30
ADR LABEL NO.	3	HAZCHEM CODE	3Y
CEFIC TEC(R) NO.	30GF1-III, 30GF1-sp	RID CLASS NO.	3
RID PACK GROUP	III	UN NO. SEA	1263
IMDG CLASS	3	IMDG PAGE NO.	3302
IMDG PACK GR.	III	EMS	F-E, S-E
MFAG	See Guide	MARINE POLLUTANT	



UN NO. AIR	1263	AIR CLASS	3
AIR PACK GR.	III		

**15 REGULATORY INFORMATION**

**LABELLING**



Irritant



Dangerous for the environment

**RISK PHRASES**

R10	Flammable.
R37	Irritating to respiratory system.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**SAFETY PHRASES**

S51	Use only in well-ventilated areas.
S57	Use appropriate containment to avoid environmental contamination.

## Anglo Flexi-Joint Fill - primer

S60	This material and its container must be disposed of as hazardous waste.
S61	Avoid release to the environment. Refer to special instructions/safety data sheets.
P4	Contains isocyanates. See information supplied by the manufacturer.

### UK REGULATORY REFERENCES

Petroleum (Consolidation) Act, as amended 1984 SI 1244. Highly Flammable Liquid Regulations 1972.

### ENVIRONMENTAL LISTING

Rivers (Prevention of Pollution) Act 1961. Control of Pollution (Special Waste Regulations) Act 1980.

### EU DIRECTIVES

System of specific information relating to Dangerous Preparations. 2001/58/EC.

### STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health.

### APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

### GUIDANCE NOTES

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

---

## 16 OTHER INFORMATION

---

REVISION DATE 08/12/2008

REV. NO./REPL. SDS GENERATED 1

### RISK PHRASES IN FULL

R10	Flammable.
R20	Harmful by inhalation.
R36/37/38	Irritating to eyes, respiratory system and skin.
R37	Irritating to respiratory system.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.