



SAFETY DATA SHEET

Anglo Flexi-Joint Fill - resin

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

| | |
|--------------|---|
| PRODUCT NAME | Anglo Flexi-Joint Fill - resin |
| SUPPLIER | Anglo Building Products Ltd RUST-OLEUM UK Ltd Unit 6, Spitfire Close Coventry Business Park Coventry CV5 6UR +44 (0) 2476 717 329 +44 (0) 2476 718 930 info.uk@ro-m.com |

2 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

3 COMPOSITION/INFORMATION ON INGREDIENTS

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

INGESTION

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Get medical attention if any discomfort continues.

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

PROTECTIVE EQUIPMENT

Anglo Flexi-Joint Fill - resin



ENGINEERING MEASURES

Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of vapours.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

HAND PROTECTION

Use suitable protective gloves if risk of skin contact.

EYE PROTECTION

If risk of splashing, wear safety goggles or face shield.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|------------------|--------------------|---------------------------------|-------|
| APPEARANCE | Viscous liquid | | |
| COLOUR | Grey | | |
| ODOUR | Mild | | |
| SOLUBILITY | Insoluble in water | | |
| RELATIVE DENSITY | 1.3 | VOLATILE ORGANIC COMPOUND (VOC) | <0.1% |

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid excessive heat for prolonged periods of time.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO₂).

11 TOXICOLOGICAL INFORMATION

INHALATION

In high concentrations, vapours may irritate throat and respiratory system and cause coughing.

INGESTION

May cause discomfort if swallowed.

SKIN CONTACT

Liquid may irritate skin.

EYE CONTACT

Spray and vapour in the eyes may cause irritation and smarting.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Not regarded as dangerous for the environment.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.



SAFETY DATA SHEET

Anglo Flexi-Joint Fill - hardener

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME Anglo Flexi-Joint Fill - hardener

SUPPLIER Anglo Building Products Ltd
 RUST-OLEUM UK Ltd
 Unit 6, Spitfire Close
 Coventry Business Park
 Coventry
 CV5 6UR
 +44 (0) 2476 717 329
 +44 (0) 2476 718 930
 info.uk@ro-m.com

2 HAZARDS IDENTIFICATION

Irritating to eyes, respiratory system and skin. May cause sensitisation by inhalation.

CLASSIFICATION R42. Xi;R36/37/38.

3 COMPOSITION/INFORMATION ON INGREDIENTS

| Name | EC No. | CAS-No. | Content | Classification |
|---|--------|-----------|---------|----------------------------|
| DIPHENYLMETHANEDIISOCYANATE -Isomers & homologues | | 9016-87-9 | 10-30% | Xn;R20. Xi;R36/37/38. R42. |

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention.

INGESTION

DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Provide rest, warmth and fresh air. Get medical attention.

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Rinse the skin immediately with lots of water. Get medical attention promptly if symptoms occur after washing.

EYE CONTACT

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

SPILL CLEAN UP METHODS

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact.

Anglo Flexi-Joint Fill - hardener

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

STORAGE CLASS

Chemical storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

| Name | Std | LT - ppm | LT - mg/m3 | ST - ppm | ST - mg/m3 |
|---|-----|----------|-----------------|----------|-----------------|
| DIPHENYLMETHANEDIISOCYANATE -Isomers & homologues | MEL | | 0.02 mg/m3(Sen) | | 0.07 mg/m3(Sen) |

PROTECTIVE EQUIPMENT



PROCESS CONDITIONS

Provide eyewash station.

ENGINEERING MEASURES

Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of vapours.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

HAND PROTECTION

Use suitable protective gloves if risk of skin contact.

EYE PROTECTION

If risk of splashing, wear safety goggles or face shield.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|------------------|--------------------|---------------------------------|-------|
| APPEARANCE | Liquid | | |
| COLOUR | Brown | | |
| ODOUR | Mild | | |
| SOLUBILITY | Insoluble in water | | |
| RELATIVE DENSITY | 1.2 | VOLATILE ORGANIC COMPOUND (VOC) | <0.1% |

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid excessive heat for prolonged periods of time.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).

11 TOXICOLOGICAL INFORMATION

INHALATION

May cause sensitisation by inhalation.

INGESTION

May cause stomach pain or vomiting.

Anglo Flexi-Joint Fill - hardener**SKIN CONTACT**

May cause sensitisation by skin contact. Irritating to skin.

EYE CONTACT

Irritating to eyes.

12 ECOLOGICAL INFORMATION**ECOTOXICITY**

Not regarded as dangerous for the environment.

13 DISPOSAL CONSIDERATIONS**DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

| | |
|----------------------|---|
| GENERAL | The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID). |
| | No transport warning sign required. |
| ROAD TRANSPORT NOTES | Not Classified |
| RAIL TRANSPORT NOTES | Not Classified. |
| SEA TRANSPORT NOTES | Not Classified. |
| AIR TRANSPORT NOTES | Not Classified. |
| MARINE POLLUTANT | No. |

15 REGULATORY INFORMATION**LABELLING**

Harmful

CONTAINS

DIPHENYLMETHANEDIISOCYANATE -Isomers & homologues

RISK PHRASES

R36/37/38 Irritating to eyes, respiratory system and skin.
R42 May cause sensitisation by inhalation.

SAFETY PHRASES

S23 Do not breathe vapour/spray.
S24/25 Avoid contact with skin and eyes.
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S37 Wear suitable gloves.
S38 In case of insufficient ventilation, wear suitable respiratory equipment.
S45 In case of accident or if you feel unwell, seek medical advice immediately (show label where possible).
S60 This material and its container must be disposed of as hazardous waste.
P4 Contains isocyanates. See information supplied by the manufacturer.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

16 OTHER INFORMATION

Anglo Flexi-Joint Fill - hardener

REVISION DATE 08/12/2008

REV. NO./REPL. SDS GENERATED 1

RISK PHRASES IN FULL

| | |
|-----------|--|
| R20 | Harmful by inhalation. |
| R36/37/38 | Irritating to eyes, respiratory system and skin. |
| R42 | May cause sensitisation by inhalation. |



SAFETY DATA SHEET

Anglo Flexi-Joint Fill - primer

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME Anglo Flexi-Joint Fill - primer

SUPPLIER Anglo Building Products Ltd
 RUST-OLEUM UK Ltd
 Unit 6, Spitfire Close
 Coventry Business Park
 Coventry
 CV5 6UR
 +44 (0) 2476 717 329
 +44 (0) 2476 718 930
 info.uk@ro-m.com

2 HAZARDS IDENTIFICATION

Flammable. Irritating to respiratory system. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION Xi;R37. N;R51/53. R10.

3 COMPOSITION/INFORMATION ON INGREDIENTS

| Name | EC No. | CAS-No. | Content | Classification |
|--|-----------|------------|---------|----------------------------------|
| 1,2,4-TRIMETHYLBENZENE | 202-436-9 | 95-63-6 | 10-30% | R10 Xn;R20 Xi;R36/37/38 N;R51/53 |
| CUMENE | 202-704-5 | 98-82-8 | 1-5% | R10 Xn;R65 Xi;R37 N;R51/53 |
| MESITYLENE | 203-604-4 | 108-67-8 | 5-10% | R10 Xi;R37 N;R51/53 |
| Solvent naphtha(petroleum), light aromatic,<0.1% benzene | 265-199-0 | 64742-95-6 | 10-30% | Xn;R65. Xi;R37. N;R51/53. R10. |

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

GENERAL INFORMATION

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INHALATION

Move the exposed person to fresh air at once. For breathing difficulties oxygen may be necessary. If breathing stops, provide artificial respiration. Keep the affected person warm and at rest. Get prompt medical attention.

INGESTION

DO NOT INDUCE VOMITING! Remove victim immediately from source of exposure. Rinse mouth thoroughly. Provide rest, warmth and fresh air. Get medical attention immediately!

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Contact physician if irritation persists.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Fire can be extinguished using: Foam. Dry chemicals, sand, dolomite etc.

SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapours. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

6 ACCIDENTAL RELEASE MEASURES

Anglo Flexi-Joint Fill - primer

SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Clean-up personnel should use respiratory and/or liquid contact protection. Absorb in vermiculite, dry sand or earth and place into containers.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Use explosion proof electric equipment.

STORAGE PRECAUTIONS

Flammable/combustible - Keep away from oxidisers, heat and flames. Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

STORAGE CLASS

Flammable liquid storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

| Name | Std | LT - ppm | LT - mg/m3 | ST - ppm | ST - mg/m3 |
|--------|-----|------------|---------------|------------|---------------|
| CUMENE | OES | 25 ppm(Sk) | 125 mg/m3(Sk) | 50 ppm(Sk) | 250 mg/m3(Sk) |

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

RESPIRATORY EQUIPMENT

Respiratory protection must be used if air contamination exceeds acceptable level.

HAND PROTECTION

Use protective gloves.

EYE PROTECTION

Use approved safety goggles or face shield.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|--------------------|-----------------------|---------------------------------|------|
| APPEARANCE | Liquid | | |
| COLOUR | Brown | | |
| ODOUR | Aromatic hydrocarbons | | |
| SOLUBILITY | Insoluble in water | | |
| BOILING POINT (°C) | >150C | RELATIVE DENSITY | 0.99 |
| FLASH POINT (°C) | 43C | VOLATILE ORGANIC COMPOUND (VOC) | 50% |

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid heat. Avoid contact with oxidisers or reducing agents.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

11 TOXICOLOGICAL INFORMATION

Anglo Flexi-Joint Fill - primer

HEALTH WARNINGS

INHALATION. May cause irritation to the respiratory system. Solvent vapours are hazardous and may cause nausea, sickness and headaches. SKIN CONTACT. Irritating to skin. Product has a defatting effect on skin. EYE CONTACT. Irritating to eyes. INGESTION. May cause discomfort.

ROUTE OF ENTRY

Inhalation. Skin absorption.

12 ECOLOGICAL INFORMATION

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION



| | | | |
|----------------------|------------------------|------------------|-----------------------------|
| UK ROAD CLASS | 3 | | |
| PROPER SHIPPING NAME | PAINT RELATED MATERIAL | | |
| UN NO. ROAD | 1263 | UK ROAD PACK GR. | III |
| ADR CLASS NO. | 3 | ADR CLASS | Class 3: Flammable liquids. |
| ADR PACK GROUP | III | HAZARD No. (ADR) | 30 |
| ADR LABEL NO. | 3 | HAZCHEM CODE | 3Y |
| CEFIC TEC(R) NO. | 30GF1-III, 30GF1-sp | RID CLASS NO. | 3 |
| RID PACK GROUP | III | UN NO. SEA | 1263 |
| IMDG CLASS | 3 | IMDG PAGE NO. | 3302 |
| IMDG PACK GR. | III | EMS | F-E, S-E |
| MFAG | See Guide | MARINE POLLUTANT | |



| | | | |
|--------------|------|-----------|---|
| UN NO. AIR | 1263 | AIR CLASS | 3 |
| AIR PACK GR. | III | | |

15 REGULATORY INFORMATION

LABELLING



Irritant



Dangerous for the environment

RISK PHRASES

| | |
|--------|---|
| R10 | Flammable. |
| R37 | Irritating to respiratory system. |
| R51/53 | Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |

SAFETY PHRASES

| | |
|-----|---|
| S51 | Use only in well-ventilated areas. |
| S57 | Use appropriate containment to avoid environmental contamination. |

Anglo Flexi-Joint Fill - primer

| | |
|-----|---|
| S60 | This material and its container must be disposed of as hazardous waste. |
| S61 | Avoid release to the environment. Refer to special instructions/safety data sheets. |
| P4 | Contains isocyanates. See information supplied by the manufacturer. |

UK REGULATORY REFERENCES

Petroleum (Consolidation) Act, as amended 1984 SI 1244. Highly Flammable Liquid Regulations 1972.

ENVIRONMENTAL LISTING

Rivers (Prevention of Pollution) Act 1961. Control of Pollution (Special Waste Regulations) Act 1980.

EU DIRECTIVES

System of specific information relating to Dangerous Preparations. 2001/58/EC.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

16 OTHER INFORMATION

REVISION DATE 08/12/2008

REV. NO./REPL. SDS GENERATED 1

RISK PHRASES IN FULL

| | |
|-----------|---|
| R10 | Flammable. |
| R20 | Harmful by inhalation. |
| R36/37/38 | Irritating to eyes, respiratory system and skin. |
| R37 | Irritating to respiratory system. |
| R51/53 | Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| R65 | Harmful: may cause lung damage if swallowed. |