



SPRAY GRIP

A clear slip resistant aerosol spray for use on ramps, steps and most floor surfaces

Suitable for use on most non-porous surfaces such as:

- **Floor tiles**
- **Terrazzo**
- **Painted floors**
- **Fibreglass**



- **Simply spray onto a clean dry surface for 'instant' slip resistance**
- **Suitable for light-medium pedestrian use**
- **Ideal for barefoot areas**

PROFESSIONAL QUALITY

PRODUCT INFORMATION

COMPOSITION AND APPEARANCE

Solvent base with epoxy additives. Dries to a clear, textured finish. May appear slightly yellow or grey on certain substrates. A test area is recommended on decorative surfaces.

AVAILABILITY

450ml unit.

COVERAGE

Approximately 1.5m² per 450ml unit.

STORAGE

For best results store at a temperature range of 20°C to 30°C prior to use.

PREPARATION

Surfaces should be clean dry and free of polish or wax.

APPLICATION

Shake the aerosol for at least one minute before use. Holding approximately 15cm from the surface apply using light even strokes (similar to spraying paint). Do not apply too thickly, two or three very thin coats produce a better finish than one thick coat.

DRYING TIME

Touch dry in approximately 30 minutes. Can be overcoated after one hour. Allow 12-24 hours for full traffic. This assumes a temperature above 15°C and good ventilation. Drying times are extended by low temperatures.

PLEASE NOTE

1. Solvent based product - suitable for use only in well ventilated areas.
2. If the spray clogs during use, clean with white spirit or similar solvent.
3. The product is not intended as a long term finish. Worn areas can be re-sprayed to maintain slip resistance. If a build-up of the product becomes dirty or unsightly over a period of time, it may be desirable to remove the old layer before re-application. This can be done using a water washable paint stripper.
4. Anglo manufactures a range of tough epoxy resin coatings which are ideal for heavy wear areas.

ORDERING

Available from stockists throughout the UK. All Anglo products are sold subject to the Company's Standard Conditions of Sale.

The Company and its representatives are often asked to comment on potential uses of Anglo products which differ from those described in the Company's data sheets. Whilst in such cases the Company and its representatives will always try to offer helpful and constructive advice, the Company cannot be held responsible for the results of such uses unless they are specifically confirmed in writing by the Company.

All information is based on results gained from experience and testing and is believed to be accurate, but it is given without acceptance of liability for loss or damage attributable to reliance thereon as conditions of use lie outside our control.

WWW.ANGLOBUILD.CO.UK

Rust-Oleum UK Ltd.

Unit 6, Spitfire Close, Coventry Business Park, Coventry, CV5 6UR, United Kingdom
T +44 (0)2476 717 329 F +44 (0)2476 718 930

info.uk@ro-m.com www.ro-m.com